

STANDARD FEATURES PROTEC Q18 CLASSIC & PROTEC Q18 VARIO



TECHNICAL DATA	
Standard Vehicle	IVECO Daily
Chassis Type	70 C 18 L
Motor	4 Cylinder
Cubic Capacity	3,0 I
Output (at 3.000 - 3.500 min-1)	180 hp
Torque Value (at 1.500 - 2.750 min-1)	430 Nm
Total Lenght (mm)	7.850
Total Width (mm)	2.330
Total Height without superstructure (mm): without alcoves / with alcoves (plus)	3.250 / 3.350
Wheelbase (mm)	4.350
Technically permissible overall mass (kg)	7.200
Additional Load (kg) depending on fittings Towing capacity (kg)	up to 1.400 up to 3.500
Seats with three-point safety belts: Q18 CLASSIC / Q18 VARIO	4 / 6
Basic price in Euros including 19% VAT. (Status as of April 2018)	218.400,00
CHASSIS IVECO DAILY	210.400,00
Standard solid paintwork	
Turbo diesel engine with rear-wheel drive and dual (twin) tyres	•
EURO 6 with particulate filter	•
Six-speed manual transition	•
Traction control system (ASR) and electronic stability program (ESP)	•
Electronically-controlled anti-blocking system (ABS)	•
Cruise Control	•
Electric window regulators for driver and passenger side	•
Generator 210 A	•
Fuel Tank 90 litre including filler neck in B-pillar	•
Heated external and electronically adjustable mirrors	•
Spare wheel with spare wheel mounting	•
Provision for trailer socket	•
Pre-installation of radio (blinded Double-DIN available)	•
Front axle load 2.700 kg	•
Fog lights with static cornering light	•
Central locking system with remote control Driver and passenger airbags	·
Deluxe driver seat, 3-way adjustable with hydraulic suspension and heatable	•
Deluxe passenger seat, 3-way adjustable with hydraulic suspension and heatable	•
Commitment fee ex works Wessling including full standard fuel tank	•
STRUCTURE	
GFK roof extension with 2 storage spaces	
Box body made of extremely stable GFK sandwich panels	
(With PU foam, wall thickness c. 44 mm, floor c. 53 mm, roof c. 54 mm)	•
Rear wall cladding and rear bumper, as well as side box flaps formed in solid GFK	•
Exterior paintwork with gelcoat protective coating similar to RAL 9001	•
Hydraulic supporting jack system with automatic leveling	•
Double glazed tinted smoke-grey plastic windows with blackout blinds and fly screens:	
2 roof windows and 5 side windows with the 1-room Q18 CLASSIC	•
2 roof windows and 4 side windows with the 2-room Q18 VARIO	_
Entrance door with window and fly screen External electrically extendable access step with safety circuit	:
Room height: 2.18 m (central body) and 2.06 m (Slide-Outs)	•
	•
GENERAL ALDE COOR AND ALD C	
ALDE 3020 gas-powered hot water central heating	•
Fresh water tank c. 290 I, insulated and heatable	•
Waste water tank c. 260 I, insulated and heatable Fuel tank 90 I built into the chassis	
All walls and ceilings except the shower covered with cream-coloured microfibre	•
High pressure laminate surface flooring	
Direct LED lighting in all rooms	•
230 Volt sockets in all rooms	•
Storage shelfs in living area, sleeping areas and bathroom	•
Sleeping areas separated from living area by walls with doors	•

Furniture and upholstered surfaces, as well as floorings by arrangement.

• = Standard equipment

Dimensions and weights are approximate measurements and can vary. Errors and technical changes are subject to modification. Only vendor parts of the highest quality are used. Manufacture of our vehicles is carried out in our main site in Wessling near Munich. Status as of April 2018.

LIVING AREA	
Seating group, when used as living space with folding bench seat:	
5 seats, 2 of which are equipped with safety belts in the 1-room Q18 CLASSIC	•
6 seats, 4 of which are equipped with safety belts in the 2-room Q18 VARIO	
Seats and upholstery covered with microfibre / material	•
Lowerable and movable table	•
Upholstery adaptable to a bed surface	•
Storage box below the seating group	•
1 wall cabinet, 195 cm length x 50 cm height x 30 cm depth	•
1 cupboard, 206 cm height x 65 cm width x 60 cm depth with drawers and doors with the 2-room Q18 VARIO	•
1 cupboard, 190 cm height x 45 cm width x 60 cm depth with drawers and doors with the 2-room Q18 VARIO	•
KITCHEN	
Worktop 125 cm length x 58 cm width with sink and gas cooker, 3-burner gas hob	•
Additional pull-out cutting board Q18 VARIO	•
Drawers, pull-out and curved door below the worktop	•
1 wall cabinet, 125 cm length x 50 cm width x 30 cm depth	•
1 kitchen cupboard, 206 cm height x 70 cm width x 40 cm depth with the 1-room Q18 CLASSIC	
1 kitchen cupboard, 206 cm height x 45 cm width x 60 cm depth with the 2-room Q18 VARIO	-
1 cupboard, 190 cm height x 55 cm width x 60 cm depth for a refrigerator with shelf and space for oven or cabinet	•
Refrigerator 160 I with separate freezer compartment, AES (automatic and manual energy selection system 12 Volt / 230 Volt / qas)	•
5 <i>,</i>	
SHOWER / WC	
Shower 1-room Q18 CLASSIC	
1 washbasin cabinet with worktop washbasin	•
1 mirror cabinet H 69 cm x B 69 cm x T 15 cm	•
Storage shelfs	•
Shower tray 70 cm length x 70 cm width	•
Shower wall between shower and anteroom	•
WC 1-room Q18 CLASSIC	
1 wall cabinet L 60 cm x H 48 cm x T 30 cm Cassette toilet	•
Small wash basin	•
Smail wash dasin Mirror	•
Shower / WC 2-room Q18 VARIO	· ·
Opening basin	•
1 mirror cabinet H 60 cm x B 72 cm x T 15 cm	•
Storage shelfs	•
Cassette toilet	•

1 mirror cabinet H 60 cm x B 72 cm x T 15 cm

Storage shelfs
Cassette toilet
Shower tray, 72 cm length x 72 cm width
Shower wall between shower and anteroom
Shower curtain

SLEEPING AREA

All beds with slatted frames and covered cold-foam mattresses

1-room Q18 CLASSIC

Double bed, 210 cm length x 160 cm width 1 wall cupboard, 160 cm length x 50 cm width x 30 cm depth 1 wall cupboard unit, 160 cm width x 60 cm depth

2-room Q18 VARIO

Each with one, height-adjustable bed, 200 cm length, for increasing the storage space below
Each bed extendable from 70 cm to 130 cm
Each with a wall cupboard, c. 200 cm length x 40 cm height x 30 cm depth

ELECTRICS

2 FI personal security automats
1 living area battery 180 Ah (AGM)
230 V automatic battery charger with electronic control, maximum loading current 35 A
Automatic charging of body battery and vehicle battery
Charge retention by external power source as well as during travel
Automatic connection and disconnection of body battery and vehicle battery
Power inverter from 12 V to 230 V, continuous output 1.800 W / top performance 3.200 W, with mains priority circuit
230 V CEE power socket in utility room, with cable feed-through in the floor to the outside
Air compressor with tank and external connection

Multi-Panel-System to oversee the followings (and others):

Fresh water tank (level in %)

Waste water tank (level in %)

Battery voltage level of vehicle and body battery

External power source (supply status 12 V or 230 V)